

LED Triproof 40W



Technical Characteristics

<i>Big Solar Code</i>	BSL 0636/04075
<i>Wattage</i>	40W
<i>Kelvin Range</i>	5000K
<i>Operating Voltage</i>	220V AC – 240V AC
<i>Total Lumen</i>	5200Lm ±5%
<i>Efficiency</i>	130Lm/W
<i>IP Class</i>	IP 65
<i>IK Class</i>	IK 10
<i>Life Span (Hours)</i>	50000 Hours
<i>Warranty (Years)</i>	5 Years
<i>Working Temperature</i>	-20 - +50 °C
<i>Power Factor</i>	≥0,9
<i>CRI</i>	≥80
<i>Material</i>	Aluminum
<i>Material Color</i>	White
<i>Class</i>	Class I
<i>Dimmable</i>	Optional
<i>Dimensions</i>	1500X85X74 mm
<i>Certificate</i>	CE (EMC-LVD) ROHS

Product Show

Housing: LED Tri-Proof Light with 6063 Aviation Aluminum housing, wavy surface, efficient heat dissipation, outstanding durability.

Cover: Milky Cover, 90% high transmittance, durable, anti-corrosive, anti-glare

LEDs: 2835SMD, high lumen, CRI>80Ra

Driver: Tuv passed, high stability isolated driver, PF>0.90

Installation

A. Ceiling Mounted Installation, Standard Installation

B. Suspended Installation

C. Linking in series

